

# Product datasheet

Specifications



## EasyLogic PM2210, Power & Energy meter, Total Harmonic, LCD display, Pulse, class 1

METSEPM2210

EAN Code: 3606480800160

### Main

Range	EasyLogic
Product name	EasyLogic PM2200
Product or component type	Power meter
Device short name	PM2210

### Complementary

Device application	Sub billing Power monitoring
Power quality analysis	total harmonic distortion
Type of measurement	Apparent power min/max, total Active and reactive power min/max, total Current min/max, avg Voltage min/max, avg Frequency min/max, avg Total current harmonic distortion THD (I) per phase Total voltage harmonic distortion THD (U) per phase Power factor min/max, avg Apparent energy total Active and reactive energy total
Metering type	Voltage U, U21, U32, U13, V, V1, V2, V3 Unbalance current Calculated neutral current Apparent power S, S1, S2, S3 Peak demand currents Current I, I1, I2, I3 Active, reactive, apparent energy (signed, four quadrant) Active power P, P1, P2, P3 Reactive power Q, Q1, Q2, Q3 Peak demand power PM, QM, SM Demand power P, Q, S
Accuracy class	Class 1 active energy conforming to IEC 62053-21 Class 1 reactive energy conforming to IEC 62053-24
Measurement accuracy	Apparent power +/- 1 % Active energy +/- 1 % Reactive energy +/- 1 % Active power +/- 1 % Voltage +/- 0.5 % Power factor +/- 0.01 Current +/- 0.5 % Frequency +/- 0.05 %
Measurement current	5...6000 mA
Measurement voltage	35...480 V AC 50/60 Hz between phases 20...277 V AC 50/60 Hz between phase and neutral 480...999000 V AC 50/60 Hz with external VT
Frequency measurement range	45...65 Hz
[Us] rated supply voltage	44...277 V AC 45...65 Hz +/- 10 % 44...277 V DC +/- 10 %

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Network frequency</b>	60 Hz 50 Hz
<b>Ride-through time</b>	100 ms 120 V AC typical 400 ms 230 V AC typical 50 ms 125 V DC typical
<b>[In] rated current</b>	1 A 5 A
<b>Maximum power consumption in VA</b>	6 VA at 277 V AC
<b>Maximum power consumption in W</b>	3.3 W (power lines (AC)) 2 W at 277 V (power lines (DC))
<b>input impedance</b>	Current (impedance <= 0.3 mOhm) Voltage (impedance > 5 MOhm)
<b>Tamperproof of settings</b>	Protected by access code
<b>Display type</b>	Backlit LCD
<b>Display colour</b>	Monochrome
<b>Display resolution</b>	128 x 128 pixels
<b>Demand intervals</b>	Configurable from 1 to 60 min
<b>Information displayed</b>	Demand current (past value) Demand current (present value) Demand power (past value) Demand power (present value) Voltage Current Frequency Energy consumption Harmonic distortion Power factor Active power Apparent power Reactive power Unbalanced in % Harmonic amplitude
<b>Control type</b>	4 x button
<b>Local signalling</b>	Red LED: output signal 1...9999000 pulse/ k_h (kWh, kVAh, kVARh) Green LED: module operating (RUN)
<b>Number of inputs</b>	0
<b>Number of outputs</b>	1 pulse
<b>POP parameter</b>	Pulse: 20 ms (5...40 V DC, 20 mA max)1...9999000 pulse/ k_h (kWh, kVAh, kVARh)
<b>Impulse duration</b>	20 ms
<b>Communication port protocol</b>	POP
<b>Sampling rate</b>	64 samples/cycle
<b>Cybersecurity</b>	Enable/disable communication ports
<b>Communication service</b>	Remote monitoring
<b>User language</b>	German English Chinese Russian Spanish Portuguese French
<b>Product certifications</b>	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 CULus conforming to CSA C22.2 No 61010-1 RCM EAC C-Tick

<b>Mounting mode</b>	Clip-on
<b>Mounting position</b>	Vertical
<b>Mounting support</b>	Framework
<b>Provided equipment</b>	1 x installation guide
<b>Measurement category</b>	Category III 480 V Category II 480...600 V
<b>Electrical insulation class</b>	Class II Double insulation
<b>Flame retardance</b>	V-0 conforming to UL 94
<b>Connections - terminals</b>	Current transformer: screw connection (bottom) 6 Voltage inputs: screw connection (top) 4
<b>Material</b>	Polycarbonate
<b>Width</b>	96 mm
<b>Depth</b>	Total : 76.09 mm Embedded : 61.64 mm
<b>Height</b>	96 mm
<b>Net weight</b>	300 g
<b>Compatibility code</b>	PM2210

## Environment

<b>service life</b>	7 year(s)
<b>IP degree of protection</b>	IP54 front: conforming to IEC 60529 IP30 body: conforming to IEC 60529
<b>Relative humidity</b>	5...95 % at 50 °C
<b>Pollution degree</b>	2
<b>Ambient air temperature for operation</b>	-10...60 °C
<b>Ambient air temperature for storage</b>	-25...70 °C
<b>Operating altitude</b>	<= 2000 m
<b>Electromagnetic compatibility</b>	Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Emission tests conforming to FCC part 15 class A
<b>Overvoltage category</b>	III

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	12.000 cm
<b>Package 1 Width</b>	9.000 cm
<b>Package 1 Length</b>	12.500 cm
<b>Package 1 Weight</b>	353.000 g
<b>Unit Type of Package 2</b>	S03

<b>Number of Units in Package 2</b>	18
<b>Package 2 Height</b>	30.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	6.970 kg
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	144
<b>Package 3 Height</b>	75.000 cm
<b>Package 3 Width</b>	60.000 cm
<b>Package 3 Length</b>	80.000 cm
<b>Package 3 Weight</b>	65.760 kg

## Logistical informations

<b>Country of origin</b>	IN
--------------------------	----

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	129 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	11 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	115 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.7 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	6599793e-9401-4187-a617-35919522fe23
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	14
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins